SEC 22 | SEC 23 SEC 22 SEC 21 S 89°54'45" W 2637.11' S 89°54'45" W 2637.11' FOUND B.L.M. WITNESS CORNER MONUMENT ON PREVIOUS SURVEY SEC 27 FOUND DUCHESNE COUNTY
ALUMINUM CAP AT SECTION
CORNER SEC 27 | SEC 26 EXISTING FENCE SET LATH ALONG LINE N 89°58'06" E 2637.46' S 89'58'06" W 2639.09' FOUND DUCHESNE COUNTY


ALUMINUM CAP AT 1/4

CORNER SET 5/8"X24" REBAR WITH
ALUMINUM CAP STAMPED "ALLRED
SURVEYING" AT 1/16 CORNER 1319.55 1319.55 FOUND B.L.M. MONUMENT AT 1/4 CORNER ON PREVIOUS SURVEY FOUND COPPER WELD
AS PER COUNTY TIE
SHEETS AT 1/4 CORNER FOUND B.L.M. MONUMENT FOUND MONUMENT SPIKE
AS PER COUNTY TIE SHEETS
AT 1/4 CORNER ON AT SECTION CORNER ON PREVIOUS SURVEY SEC 28 | SEC 27 SEC 27 | SEC 26 S 89°55'27" E 2641.78' N 89°59'39" W 2640.92' SEC 33 SEC 34 SEC 34 SEC 35

RECORD OF SURVEY FOR

GREG TODD

SECTION 27, TOWNSHIP 1 SOUTH, RANGE 3 WEST UINTAH SPECIAL BASE & MERIDIAN



LEGEND AND NOTES

FOUND SECTION CORNER

FOUND QUARTER CORNER

- ♦ FOUND OR SET 1/16 CORNER
- FOUND REBAR OR IRON RODS SET ON PREVIOUS SURVEYS
- 5/8"X24" REBAR WITH PLASTIC CAP STAMPED ALLRED SURVEYING SET BY THIS SURVEY
- O EXISTING FENCE CORNER
- *** * * * EXISTING FENCES

INDICATES SURVEY POINT NUMBERS OF MONUMENTS FOUND AND USED

THE BASIS OF BEARINGS FOR THIS SURVEY IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT THE SW CORNER OF SECTION 27, T1S, R3W, U.S.B.&M. AS MONUMENTED BY A MONUMENT SPIKE SET IN THE ASPHALT OF THE COUNTY ROAD: LAT: 40°21'33.88695"N AND LONG: 110°13'06.20894"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER.

NARRATIVE

This survey was performed at the request of Greg Todd in order to find and locate on the ground the North line of the NW¼ of the SW¼ of Section 27.

The monuments used for this survey marking the Public Land Survey System (PLSS) corners were found as noted on the plat and used to control this survey. The Standard Section Subdivision procedure was used to determine the position of the aliquot part corners within the section.

This plat represents a dependent resurvey and a subdivision of portions of Section 27, and is designed to restore the PLSS corners to their true original locations according to the best available evidence and according to the data returned on the official General Land Office Plat.

The Basis of Bearings for this survey is based on WGS-84 datum which gives a bearing of North 89°59'39" West between the Southeast Section Corner and the South ¼ Corner of said section.

SURVEYOR'S CERTIFICATE

I, JERRY D. ALLRED, DUCHESNE COUNTY, UTAH, DO HEREBY CERTIFY THAT I AM A PROFESSIONAL LAND SURVEYOR AND THAT I HOLD CERTIFICATE NUMBER 148951 AS PRESCRIBED BY THE STATE OF UTAH. I FURTHER CERTIFY THAT THIS PLAT WAS PREPARED FROM THE FIELD NOTES AND ELECTRONIC DATA COLLECTOR FILES OF AN ACTUAL SURVEY MADE BY ME OR UNDER MY PERSONAL SUPERVISION AND THAT THE MONUMENTS INDICATED WERE FOUND OR SET DURING SAID SURVEY, AND THAT THIS PLAT ACCURATELY REPRESENTS SAID SURVEY TO THE BEST OF MY KNOWLEDGE AND BELIEF.



COUNTY SURVEYOR FILE NO. 3649 JERRY D. ALLRED & ASSOCIATES, INC. SURVEYING CONSULTANTS 1235 NORTH 700 EAST——P.O. BOX 975 DUCHESNE, UTAH 84021 (435) 738—5352

28 NOV 2017 17-100-068